

Epatec

	eTC	eTC-2300*	eTC-2300 M*	eTC-2300 H	eTC-2300 JSK	eTC-3800	eTC-3850	eTC-3851
CPU	Vortex86	Vortex86 SoC				VIA ED800		
speed	200 MHz	200 MHz				800		
MB RAM	128 MB	128 MB				256		
optional up to	-	-				-		
graphic board		Shared system memory area 8 MB				Integrated VIA UniChrome 2D		
resolution		1280x1024				1280x		
audio	AC97 CODEC	AC 97 CODEC compliant with V2.1				VIA VT1612A AC		
EIDE (Ultra DMA 133, 44Pin 2.0)	1	1	1	1	1	1	1	2
P/S 2	2	1 with Y-cable	1 with Y-cable	1 with Y-cable	1 with Y-cable	2	2	2
printer (parallel)	-	-	-	-	-	-	1	1
RS232 (serial)	optional	-	-	-	2	-	1	optional
USB 1.1	3	3	3	3	3	-	-	-
USB 2.0	-	-	-	-	-	2	2	2
CompactFlash slot	-	1	1	1	1	-	-	1
Mini PCI socket	-	-	-	-	-	-	-	1
LAN 10/100	1	1	1	1	1	1	1	1
LAN chipset						VIA VT6103	VIA VT6103	VIA VT6103
WLAN						-	-	on request
2,5" harddisk installation kit	yes	-	-	yes	-	-	yes	yes
Smart Card reader	-	-	-	-	-	-	-	-
size	133 x 63 x 111	115 x 115 x 35 mm				170x124x38	170x124x38	
weight	500 gr	500 gr				780 gr	780 gr	

eTC-3852*	eTC-3853	eTC-3854	TC3520	TK3370	*available on request
EN Nano			AMD Geode	VIA EDEN	CPU
MHz			333 MHz	1 Ghz	speed
MB			128 MB	256 MB	MB RAM
			512 MB	1024 MB	optional up to
D/3D with MPEG2 Accelarator				83697HF AGP8X	graphic board
x1024			VGA	VGA	resolution
C 97 2.2 onboard			onboard	AC97VIA VT1612A	audio
1	1	1		1	EIDE (Ultra DMA 133, 44Pin 2.0)
2	2	2	1 with Y-cable	2	P/S 2
1	1	-	1	1	printer (parallel)
optional	optional	optional	1	1	RS232 (serial)
-	-	-	4	-	USB 1.1
2	2	6	-	4	USB 2.0
1	1	1	1	1 intern	CompactFlash slot
1	-	1	1		Mini PCI socket
2	2	1	1	1	LAN 10/100
VIA VT6103+Realtek 8100B		VIA VT6103			LAN chipset
on request	-	on request	optional	optional	WLAN
-	yes	-	-	optional	2,5" harddisk installation kit
-	-	-	optional	optional	Smart Card reader
70 x 124 x 56 mm			237 x 173 x 37	232 x 51 x 202	size
900 gr			800 gr	2,2 kg	weight